

## TECHNICAL DATA : SMV 22-1200 B

<b>LIFTING DATA</b>		
Lifting capacity / Load center (up to 9000 mm / standard mast)	kg / mm	22000 / 1200
Lifting speed, unloaded / at rated load	m/s	0,30 / 0,25
Lowering speed, unloaded / at rated load	m/s	0,40 / 0,40
<b>DRIVING DATA</b>		
Drive speed forward, unloaded / at rated load	km/h	29 / 27
Drive speed reverse, unloaded / at rated load	km/h	29 / 27
Incline (driving ability) at rated load at 0 km/h/at 2 km/h	%	37 / 28
Towing (power ability) at rated load at 0 km/h/at 2 km/h	kN	196 / 147
<b>SERVICE WEIGHT / AXLE PRESSURE</b>		
Service weight	kg	32000
Axle pressure front, unloaded / at rated load	kg	16700 / 50500
Axle pressure rear, unloaded / at rated load	kg	15300 / 3500
<b>ENGINE (electronic controlled)</b>		
Engine make / model name		Volvo TAD-722-VE/HT
Emission approval EU / US		St II / Tier 2
Monitoring / emission controlled / CanBus		Yes / yes / yes
Fuel / type of engine / intercooler		Diesel/4-stroke/ yes
Power ISO 3046 / at speed	kW / rpm	180 / 2300
Torque ISO 3046 / at speed	Nm / rpm	1050 / 1400
Displacement / No. of cylinders / type	L / /	7,2 / 6-cyl / Inline
Fuel consumption, normal driving	L/h	10 – 12
Alternator, type/power	W / Amp	AC / 1540 / 55
Starting battery, voltage/capacity	V / Ah	2 x 12 / 140
<b>TRANSMISSION (electronic controlled)</b>		
Transmission make / model name		Dana TE-17300
Monitoring / reverse protection / CanBus		Yes / yes / yes
Clutch, type		Torque converter
Transmission type / type of shift gear		Softshift – Powershift / Automatic
No. of gears, forward/reverse		3 / 3
<b>DRIVE AXLE &amp; STEER SYSTEM</b>		
Drive axle make / model name		Kessler D91
Drive axle type / drive axle width	/ mm	Differential + hub reduction / 3020
Service brake system, type / affected wheels		Oil cooled Wet Disc Brakes / drive wheels
Parking brake system, type / affected wheels		Dry disc brake / spring release / drive wheels
<b>STEER AXLE &amp; STEER SYSTEM</b>		
Steer axle make / type		Konecranes / double acting single cylinder
Steering system		Hydraulic servo assisted / power steering
<b>WHEELS</b>		
Number of wheels, front+rear / Type (*driven)		4*+2 / pneumatic
Tire pressure front / rear	MPa	0,9 / 0,9
Tire dimensions (Ply rating) front / rear	Inch (No)	14.00 x 24" (PR 24) / 14.00 x 24" (PR 24)
Rim dimension front / rear	Inch	10.00 x 24"/HD / 10.00 x 24"/HD
<b>HYDRAULIC SYSTEM</b>		
Hydraulic pump make / model name		Parker & Hannifin / P2-series
Hydraulic system / pump type		Load sensing system / variable piston pump
Power-on-demand / Low energy		Yes / yes
Hydraulic oil pressure mast	MPa	22
<b>TANK VOLUMES</b>		
Diesel tank volume	L	336
Hydraulic tank volume	L	368
<b>LIFTING EQUIPMENT</b>		
Lift mast make / model		Konecranes / Duplex standard
Lift mast type / design		2-stage / free visibility
Fork carriage make / model		Konecranes / integral double forks
Fork carriage type		Hydraulic side shift & fork positioning
<b>OTHERS</b>		
Noise level (inside Cab / Lm) DIN 45635	dB(A)	70
Noise level (inside Cab/ LpAZ) EN 12053	dB(A)	75
Noise level (outside at 7 m/ Lwa) 2000/14/EC	dB(A)	110
<b>NORMS &amp; STANDARDS</b>		
Machine Directive in Europe	98 / 37 EC	Yes
Stability of Industrial Trucks	ISO 1074	Yes
Safety of Industrial Trucks	EN 1551	Yes

# TECHNICAL DATA

## SMV 22-1200 B

