



• HIGH REACH TELEHANDLER •

**GTH™-844**



#### CHARACTERISTICS

- Right-side mount engine provides enhanced visibility
- Ergonomic operator's station features tiltable steering wheel, single-lever joystick control, and new gauge and switch packages.
- Redesigned axles for enhanced steering geometry
- Proportional frame-leveling chassis — pick up or place loads on up to 10° side slopes
- Multi-function proportional joystick control for fast, precise load positioning
- Three selectable steering modes: front-wheel, coordinated and crab steer
- Power-assisted steering
- Turbocharged diesel engine
- 3-speed forward and reverse powershift transmission
- High-efficiency/variable displacement hydraulic pump
- ROPS/FOPS canopy (ISO compliant)



#### SPECIFICATIONS

Maximum lifting height	mm	13.360
Maximum forward reach	mm	8.590
Maximum lifting capacity	kg	3.629
Power source		Deutz TCD 3.6 turbo charged diesel, T4i 99 HP (74 kW) Perkins 854E turbo charged diesel, T4i 99 HP (74 kW) Perkins 1104D turbo charged diesel, T3i 99 HP (74 kW)
Drive speed	km/h	27.4
Weight*	kg	10.251

\*Weight depends on options

CONTACT YOUR NYKEI PARTNER FOR AN  
OVERVIEW OF THE AVAILABLE ATTACHMENTS:  
**info@nykei-wa.com**